




A	FOR CONSTRUCTION	EK	25.02.14
REVISIONS			



### FOOTING OPTION A - BORED PIER



## FOOTING OPTION B - PAD FOOTING




## FOOTING OPTION C - EXISTING SLAB

WIND RATED TO W33

## NOTES

- 1: THIS FOOTING DETAIL IS SUITABLE FOR FOUNDING IN NATURAL UNDISTURBED MATERIAL WITH A MINIMUM ALLOWABLE BEARING CAPACITY OF 100kPa.
- 2: IF FOOTING IS IN FILL MATERIAL PLEASE REFER TO SKYSPAN UMBRELLA FOR SITE SPECIFIC FOOTING DESIGN.
- 3: THIS FIXING DETAIL IS NOT APPLICABLE FOR CANTILEVER UMBRELLAS.
- 4: ALL WORKMANSHIP AND MATERIALS TO BE IN ACCORDANCE WITH AS3600.
- 5: EXCAVATIONS TO BE CLEAN + FREE FROM LOOSE MATERIAL.
6. CONCRETE  $f'c = 25MPa$ .
7. MAXIMUM AGGREGATE SIZE TO BE 20mm.
8. CONCRETE SHOULD BE VIBRATED AFTER POURING, AND KEPT DAMP FOR AT LEAST 7 DAYS TO ASSIST CURING.



## TYPICAL H.D. BOLT DETAILS

4/M12 Gr4.6 GALV. H.D. BOLTS 110 MIN EMBEDMENT 100  
MIN EDGE DISTANCE USE RAMSET 101 RESIN OR EQUIV.

**OR**

POWERS EXCALIBUR SCREWBOLT - MIN 90 EMBEDMENT  
100 MIN EDGE DISTANCE

OR

THREADED INSERT ANCHORS WITH M12 SOCKET HEAD  
CAP SCREWS BOLT HEAD TO BE FLUSH WITH SLAB  
WHEN UMBRELLA REMOVED

ALL FIXINGS TO BE INSTALLED IN ACCORDANCE WITH  
MANUFACTURERS INSTRUCTIONS

<b>Project Name</b> 4m x 3m RECTANGULAR HORIZON UMBRELLA	This document is copyright and remains the property of Skyspan Shade Pty. Ltd It must not be used or copied without the written consent of Skyspan Shade Pty. Ltd.			
	<b>Date:</b> FEB 14	<b>Drawn:</b> EK	<b>Checked:</b> GM	<b>Scale:</b> A4: NTS
<b>Title</b> GENERAL ARRANGEMENT WITH FOOTING DETAILS	<b>Drawing No.</b> <div>H43R-1001</div>			<b>Revision</b> <div>A</div>